

Aquatec Floor Care Series

Made in the USA

Quality, Innovation and Service



25 years designing and manufacturing the highest quality and most dependable diaphragm electric pumps



Designed for Floor Care Solution Spray, Pumpout and Truckmount Transfer Applications

- Made in USA with Superior Design and Quality
- Demand Switch & Internal Bypass to Eliminate Cycling
- Sealed Motors to Prevent Moisture Intrusion
- Self Priming and Capable of Running Dry
- Global Standards & Approvals
- Drop-in Replacement to Competitor's Pumps
- Maintenance Free
- Available in 12Vdc, 24Vdc, 36Vdc, 115Vac and 230Vac
- Customization and Private Labeling are Available



Aquatec Floor Care Series

Made in the USA

Quality, Innovation and Service

www.aquatec.com



About Aquatec

Founded in 1988, and headquartered in Irvine California, Aquatec remains committed to manufacturing excellence by adhering to stringent production standards and rigorous QA procedures. Aquatec products are globally distributed throughout several industries including floor care.

The Aquatec Floor Care Series is available through OEM and distribution partners. Please contact Aquatec at (949) 225-2200 for additional details.

- **Solution Spray pumps in 60, 120, 170 & 220psi** (customization available)

Performance Characteristics									
Nozzle Size	58-FLC-120			58-FLC-170			58-FLC-220		
Orifice	Pressure (PSI)	Flow (GPM)	AMPS 115Vac 230Vac	Pressure (PSI)	Flow (GPM)	AMPS 115Vac 230Vac	Pressure (PSI)	Flow (GPM)	AMPS 115Vac 230Vac
Number 2	95	0.25	0.95 0.48	145	0.50	1.36 0.68	175	0.55	1.55 0.76
Number 4	83	0.65	0.92 0.46	120	0.80	1.26 0.63	130	0.84	1.37 0.68
Number 6	70	0.80	0.84 0.42	90	0.98	1.09 0.55	90	0.98	1.16 0.58

- **Pumpout pumps in 3.5 and 5.5 GPM** (customization available)

Performance Characteristics						
Pressure	Aquatec 3.5			Aquatec 5.5		
PSI	Flow (GPM)	AMPS 115Vac 230Vac	Flow (GPM)	AMPS 115Vac 230Vac	Flow (GPM)	AMPS 115Vac 230Vac
70	1.60	1.32 0.65	2.90	2.10 1.05		
60	1.75	1.20 0.60	3.05	1.95 0.97		
50	1.90	1.07 0.53	3.33	1.80 0.90		
40	2.15	0.95 0.47	3.60	1.60 0.80		
30	2.40	0.83 0.41	4.00	1.42 0.71		
20	2.69	0.70 0.35	4.50	1.20 0.60		
10	3.10	0.57 0.27	5.00	0.97 0.48		
OPEN FLOW	3.50	0.47 0.24	5.50	0.89 0.45		

- **Truckmount transfer pumps in 4.2 GPM** (customization available)

Performance Characteristics		
Pressure	Aquatec 4.2	
PSI	Flow GPM	AMPS 12Vdc
70	2.50	15.00
60	2.65	14.00
50	2.80	12.80
40	3.00	11.20
30	3.25	9.80
20	3.50	8.00
10	3.90	6.20
OPEN FLOW	4.25	5.00



aquatec

ISO 9001:2008

17422 Pullman Street
Irvine, CA 92614
USA
800 975-9995
949 225-2200
Fax 949 225-2222
www.aquatec.com

Aquatec Floor Care products meet agency requirements and are ROHS compliant.